

**DYMAX  
CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**PRODUCT VL300**

51 Greenwoods Rd., Torrington, CT 06790

Phone: (860) 482-1010

Fax: (860) 482-1308

---

**I. Product Identification.**

Product:	<b>VL300</b>	<u>NFPA Est.</u>	<u>HMIS Est.</u>
Synonyms:	Polyurethane Oligomer Mixture	Health: 2	Health: 2
		Fire: 1	Flam: 1
		React: 1	React: 1

**II. Composition.**

<u>Ingredient</u>	<u>Concentration %</u>	<u>C.A.S. number</u>	<u>ACGIH TLV</u>
High Boiling (Meth) Acrylate	20-30	PROPRIETARY	--
High Boiling (Meth) Acrylate	25-35	PROPRIETARY	--
Cellulose Ester	5-10	PROPRIETARY	--
Photoinitiator	1-4	947-19-3	--
Acrylic Acid	5-10	79-10-7	2 ppm
Urethane Acrylate Oligomer	27-38	PROPRIETARY	--

**III. Chemical and Physical Properties.**

Vapor Pressure:	6 mm Hg at 30° C	Vapor Density:	Heavier than Air
Solubility in Water:	Insoluble	Specific Gravity:	1.08
Boiling Point:	N. A.	Appearance:	Amber Liquid
Odor:	Mild		

**IV. Flammability and Explosive Properties.**

Flash Point: > 200° F (P.M.C.C.)

Recommended Extinguishing Agents: Use water spray, foam, dry chemical, or CO<sub>2</sub>

Hazardous Products Formed by Fire or Thermal Decomposition: Toxic fumes (oxides of carbon and nitrogen) may be evolved upon exposure to heat or open flame.

Unusual Fire or Explosion Hazards: None.

Compressed Gases: None. Pressure at Room Temperature: N.A.

**V. Reactivity Data.**

Stability:	Stable.	Hazardous Polymerization:	May occur.
Hazardous Decomp. Prod:	None.		
Incompatibility:	Oxidizers, amines, strong Lewis or mineral acids, thiosulfates. Smoke and toxic fumes may be evolved as a result of uncontrolled exothermic reaction of large masses of material reacting with curing agents, such as peroxides, amines, or exposure to light.		

**VI. Spill or Leak Procedures.**

Dike area to prevent spreading. Absorb on vermiculite, sand or other inert absorbing material. Dispose of as a chemical waste in accordance with current local, state, and federal regulations.

**DYMAX  
CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**PRODUCT VL300**

**VII. Storage and Handling Procedures.**

Storage: Avoid storage over 100° F, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.  
Handling: Avoid prolonged or repeated breathing of vapor.

**VIII. Shipping Regulations.**

DOT and IATA Hazard Classification: Not Restricted Article  
Proper DOT Shipping Name: Not Applicable  
Identification Number: DOT – None IATA – None

**IX. Emergency Treatment Procedures.**

Eye Irritation: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.  
Skin Contact: In case of skin contact, wash thoroughly with soap and water. Do not use organic solvents for cleanup as they may dry or irritate the skin and act as a carrier for chemical absorption.  
Inhalation: Remove affected person to fresh air.  
Ingestion: Low toxicity; Get medical attention.

**X. Personal Protection.**

Respiratory: Positive fresh air exhaust should be provided in the work area; respiratory equipment is unnecessary in normal use.  
Skin: Avoid skin contact. Wear gloves and impervious protective clothing if frequent direct contact is likely.  
Eyes: Do not wear contact lenses. Chemical safety goggles are recommended.

**XI. Health Hazard Data.**

Potential Routes of Entry: Skin, eyes, inhalation.  
Symptoms of Overexposure: Possible skin and eye irritation on contact. Inhalation of vapors in an unventilated area may, over time, induce headaches.

Exposure Limits: ACGIH OSHA OTHER  
(TLV) (PEL)

Ingredients  
Acrylic Acid 2 ppm -- --

	<u>Target Organs:</u>	<u>NTP</u>	<u>Carcinogen:</u>	<u>OSHA</u>
High Boiling (Meth) Acrylate	--	NO	<u>IARC</u> NO	NO
High Boiling (Meth) Acrylate	--	NO	NO	NO
Cellulose Ester	--	NO	NO	NO
Photoinitiator	--	NO	NO	NO
Acrylic Acid	--	NO	NO	NO
Urethane Acrylate Oligomer	--	NO	NO	NO

Abbreviations:  
N/A – Not Applicable ALG – Allergen  
IRR – Irritant KID – Kidney  
LIV – Liver REP – Reproductive

**DYMAX  
CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**PRODUCT VL300**

**XII. Regulatory Information.**

SARA Listed Ingredients:  
ACRYLIC ACID

TSCA Inventory: Yes

**STATE RIGHT-TO-KNOW**

**California Proposition 65**

This product does not contain materials which the State of California has found to cause cancer, birth defects, or other reproductive harm.

**Massachusetts** Right-to-know, Substance List (MSL) Hazardous Substances and Extraordinary Hazardous Substances on the MSL must be identified when present in products. Components present in this product at a level, which could require reporting under the statute, are:

\*\* NONE \*\*

**Pennsylvania** Right-to-know, Hazardous Substance List Hazardous Substances and Special Hazardous Substances on the list must be identified when present in products. Components present in this product at a level, which could require reporting under the statute, are:

\*\* NONE \*\*

Other Regulatory Information:

\*\* NONE \*\*

Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists.  
OSHA = Occupational Safety and Health Administration.  
TLV = Threshold Limit Value.  
PEL = Permissible Exposure Limit.  
NTP = National Testing Program.  
IARC = International Agency for Research on Cancer.  
NFPA = National Fire Protection Association.  
HMIS = Hazardous Materials Identification System.  
-- = No Data / Not Available.

**XIII. Preparation Information.**

Prepared By: Stephen E. Cantor, Ph.D.  
Title: Laboratory Manager  
24 Hr. Telephone: CHEMTREC 1-800-424-9300

**REVISION DATE:** MARCH 24, 1999

---

To the best of our knowledge, the information contained herein is accurate. However, Dymax Corporation does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.